


XBC RANGE

XXXXXXXXXXXXXXXXXXXX

Floor-standing Box Compression machines with full computer control and precision AC servo drive system. Rigid 4-column load frame with lower platen mounted on 4 balanced load cells for improved accuracy and tolerance of uneven loading.



	XBC1000-25	XBC1000-50	XBC1250-25	XBC1250-50	XBC1500-25	XBC1500-50
Force Capacity kN	25	50	25	50	25	50
Accuracy	Better than +/- 0.5% of reading down to 1/1000th of load cell capacity					
Platen size mm	1000 x 1000	1000 x 1000	1250 x 1250	1250 x 1250	1500 x 1500	1500 x 1500
Max Platen Opening mm*	1050	1050	1300	1300	1550	1550
Position Control Resolution mm	0.000001	0.000001	0.000001	0.000001	0.000001	0.000001
Distance between columns mm	1090	1090	1340	1340	1590	1590
Minimum Speed mm/min	0.00001	0.00001	0.00001	0.00001	0.00001	0.00001
Maximum Speed mm/min	500	500	500	500	500	500
Speed Accuracy	+/- 0.1% under stable conditions					
Max force at full speed kN	25	50	25	50	25	50
Max speed at full load mm/min	500	500	500	500	500	500
Data Acquisition Rate (at PC)	500Hz as standard (optional 1000Hz)					
PC Connection	Ethernet (or USB via adaptor)					
Machine Configuration	Four column configuration, floor-standing					
Weight kg	630	690	850	920	1350	1430
Operating Temperature °C	-10 to +40					
Operating Humidity	+10 to +90% non-condensing					
Electrical Supply	Dual input selectable 115 or 230V, 1ph 50/60Hz					
Power kW	1	1	1	1	1	1

* Extended travel versions available on request.

Made to measure



Fully digital testing system with high precision control and accuracy, includes automated computer control of test methods giving simplicity of operation.

High resolution load cells with accuracies better than +/-0.5% down to 1/1000th of the load cell capacity.

Automatic recognition of load cells and extensometers, with on-device storage of calibration parameters.

Software calibration check facility for instant verification of machine accuracy.

800% overload capability of load cells without damage.

High efficiency pre-loaded self cleaning ballscrews for fast, quiet testing. Fitted with sealed for life lubricated end bearings.

Crosshead guidance system providing precise alignment and smooth running.

Precision crosshead control via digital AC servo drive and brushless servo motor giving maintenance free operation and 23-Bit positional control.


High speed data collection systems for up to 4 synchronous channels.

6 I/O channels for additional devices such as extensometers, micrometers, calipers, balances etc.

High stiffness loading frames with precision ground steel guide rods and rigid extruded support columns with T-slots for accessory mounting.


Overload, overtravel and impact protection.

Telescopic covers giving additional protection for ballscrews against dust and testing debris.




1. Available at additional cost. Machine can alternatively be controlled using a standard PC or laptop (not supplied).

XBC Dimensions




	XBC1000-25/50	XBC1250-25/50	XBC1500-25/50
Overall Width 'A' (excluding touchscreen)	1455	1705	1955
Depth 'B'	1010	1260	1350
Overall Height 'C'	1780	2030	2280
Distance between columns 'D'	1090	1340	1590
Platen Width/Depth 'E'	1000	1250	1500
Maximum Platen Opening 'F'	1050	1300	1550


Notes: All dimensions in mm
Dimensions based on standard models, extended/wide-frame versions available on request.



Large range of grips and fixtures available



High-speed modular electronics



Accessories according to ISO, ASTM and TAPPI standards.

Built for precision



Force Measurement

Universally Calibrated, better than Grade 0.5 EN 7500-1, DIN 51221 ASTM E-4, AFNOR A03-501. Range 0.4% to 100% minimum. Automatic identification of load cell. Resolution 1 part in 500000. Electronic load cell protection.

Extension Measurement

Full frame length to a maximum resolution of 0.000001mm (selectable). Accuracy +/- 0.01mm. Absolute, relative and auxiliary modes in mm, inch and percent.

Speed Control

Class-leading low speed performance with speeds down to 0.00001mm/min. Drive system temperature and current protection.

Load Frame

Rigid 4-column load frame with precision crosshead guidance. Frame stiffness up to 150kN/mm plus K factor facility built-in. Re-circulating ball screw with bellows. Electronic limit trips, total travel trips and customer programmable safety stops.

Electronics System

Modular electronics system offers fast data transfer to the PC (up to 1000Hz) via high-speed Ethernet connection. Extensive input options allow the connection of a wide range of extensometers and accessories via simple plug-in interface modules.

Safety Features

Extensive safety features to ensure highest levels of operator safety, including E-Stop, programmable extension limits and overload/impact detection. Fully compliant with global safety directives:- 2006/42/EU Machinery Directive, 2014/35/EU Low Voltage Directive and 2014/30/EU Electromagnetic Compatibility Directive.

Optional Touchscreen Panel PC

When paired with the optional IPC3 industrial-grade Panel PC with touchscreen control, the machine becomes a robust standalone system without the need for an external PC or Laptop.

Using the latest Windows 10 operating system and running a full version of Testometric's winTest software the system allows complete control of the test machine and provides storage and access to unlimited test methods and results. The included mounting arm which attaches to the machine column T-Slots is fully adjustable for height, reach and viewing angle allowing the user to find the most ergonomic working position.

Specification:-

Display 15.4" 1280x800, 24 bit full colour panel with projected capacitive touch screen and anti-reflective, dirt repellent screen protection.


2xUSB3.0, 2xUSB2.0, 3xGigaLAN.

CPU-i5-7300U Intel Core i5 Processor, 2.6GHz.

8GB RAM (non-ECC)

128GB CFast MLC storage (SSD), SATA III 6GB/s

Microsoft Windows 10 IoT Enterprise LTSC - 64-Bit.



Tried and tested software




All Testometric models are supplied with our comprehensive winTest Analysis software package.

The product of many years of continuous development, winTest Analysis provides a flexible and intuitive software package to suit all types of material testing. With built-in test methods covering tensile, compression, flexural, peel, shear, tear, cyclic, creep and multi-stage tests.


It includes a wide range of industry standard test methods and the facility to create and store an unlimited number of further test methods. There is automated storage of all test data and ease of export to other software packages such as word, excel, access and SPC systems for enhanced report generation.

Please refer to the winTest software datasheet for further information.

With the addition of the RCE remote connection option all machines can be web-linked directly to Testometric for remote investigation, monitoring and software upgrades. Please refer to the RCE datasheet for more information.



Real time test screen



Test analysis screen



Standing the test of time



Testometric is a private limited company that has been involved in the design and manufacture of testing machines and quality control equipment since its foundation in 1970.

Fifty years of continuing development has resulted in a main product line of universal strength testing machines for tension, compression, flexure, shear and product testing. Testometric machines are used in over 100 countries worldwide and supported by a network of offices and approved agencies.

Testometric is established in all industries and educational sectors and we have an enviable reputation for innovation, product quality and excellent customer support.

testometric.co.uk